



Three Roll Mill

Practical and well dispersed!

TRS SERIES

Manual Three Roll Mill

Application: Mainly used in Soap, paint, cosmetics, pigment, lubricant grease, carbon fiber and so on...

Feature

- Chain gears driving, oil tank gear box, fewer noise, longerlife time.
- Hydraulic cylinder drive, pressure guage to show the rollpressure
- SUS304 discharge hopper

Equipment details

- 1 Cooling system
- 2 Baffle
- 3 Hand wheel for adjust gap of roll
- 4 Scraper knife
- 5 Lifting adjustment



Optional configuration table

Configuration table		
● Standard / ○ Optional		
Material of body frame	Stainless steel	○
	Carbon steel	●
Adopting gap adjusting		●
Topple over device hopper		○
Chamber		○
Inverter control		○
Baffle material (metal or teflon)		○

Technical parameter

Model	Roller diameter (mm)	Working length (mm)	Roller Speed(rpm)			Main motor power (kw)	Weight (kg)	Overall size (mm)
			Slow	Middle	Fast			
TRS5"	120	280	26	70	186	1.5	400	830x750x920
TRS6"	150	300	38	87	203	2.2	500	1070x880x950
TRS8"	200	600	22	67	200	5.5	1500	1380x910x1080
TRS9"	260	675	27	76	217	7.5	2300	1800x1400x1180
TRS12"	305	760	22.5	70	217	11	3800	2100x1550x1230
TRS16"	406	810	19	58	178	15	5300	2050x1810x1500
TRS16" L	406	1000	19	58	178	22	5800	2250x1810x1500

Other configurations



TRM



TRX



TRQ

Your Best Chemical Production Line Manufacturer in China



FRANLI MACHINERY CO.,LTD

Tel:+86 15306118977

E-mail:Judy@franli.com

Add:Maker Space-5,Science &
Education Town,No.18Changwu
Middle Road, China

FRANLI®

www.franli.com